

Issue Date: 3 June 2013 Page 1 of 7

Version No.: 01 (Supersedes Version: 00)

Last Revision Date: 10 Nov 2010 **Product No.:** BW-64

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

1.1 Product Name AUTO X-RAY FIXER REPLENISHER PART B

1.2 Product Code: 833505 / 725103 873505 / 725103

1.3 Recommended Use and Restriction on Use: For the automatic processing of medical X-Ray film.

1.4 Manufacturer: FUJIFILM Asia Pacific Pte. Ltd.

UEN: 199301558N

1.5 Address: 15 Tuas Avenue 7 Singapore 639270

1.6 Business Phone Number: (65) 6862 2116 (Operating hours: 0830-1730 hours Mondays-Fridays)

Fax: (65) 6861 4829

Emergency Phone Number: (65) 6863 8753

SECTION 2: HAZARDS IDENTIFICATION

2.1 GHS Classification:

Hazard Class	Hazard Category	Hazard Statement
Corrosive to metals	Category 1	May be corrosive to metals.
Skin corrosion/irritation:	Category 2	Causes skin irritation.
Serious eye	Category 2	Causes serious eye irritation.
damage/irritation:		·

2.2 GHS label elements Pictograms:





2.3 Signal Word: Warning

2.4 Precautionary Statements:

Prevention

Keep only in original container.

Wash your hands and face thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. Absorb spillage to prevent material - damage.

Storage

Store in corrosive resistant container with a resistant liner.

2.5 Disposal:

None.



Issue Date: 3 June 2013 Page 2 of 7

Version No.: 01 (Supersedes Version: 00)

Last Revision Date: 10 Nov 2010 **Product No.:** BW-64

Other Hazards Which Do Not Result in Classification

Primary Hazards

None.

Other Hazards Which Do Not Result in Classification

Primary Hazards

None.

Specific Hazards

None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance or Preparation: This product is a mixture.

Chemical Name	CAS No.	% by Weight
Water	7732-18-5	70 - 90
Aluminum sulfate	10043-01-3	15 - 30

SECTION 4: FIRST-AID MEASURES

4.1 Inhalation:

- Move the victim into the fresh air, keep him or her warm and quiet, cover with a blanket, and send for immediate medical assistance.
- If the victim is not breathing or is breathing very weakly, loosen his or her clothing in order to secure an airway and begin artificial respiration.
- If the casualty is unconscious, but breathing, or is conscious but experiencing breathing difficulties, the provision of oxygen is effective. It is preferable to do this under medical supervision.
- No medicine other than oxygen may be dispensed. No food may be given to the victim without the physician's direction.

4.2 Skin Contact:

- If it is spilled on the skin, wash off with copious amounts of soap and water.
- Remove the contaminated clothes, shoes, etc., immediately. Cut the clothing off if necessary.
 Subsequently, rinse the skin with cool or tepid running water for at least 30 minutes.
- Immediate medical attention is required.

4.3 Eye Contact:

- If a contact lens is in place, remove it and wash the eye with warm running water for at least 15 minutes, unless the lens is firmly attached to the eye. Use physiological saline if it is readily available.
- Do not stop rinsing the eye. During the rinse, open the eyelid with your fingers so that water can reach under the eyelid. Send for an ophthalmologist immediately. An ophthalmological examination is absolutely essential because the possibility exists that there may be after effects even if there are no immediate pain or vision problems.

4.4 Ingestion:

- If it is swallowed, call a doctor immediately.
- Do not attempt to make the victim vomit.
- Rinse the mouth out thoroughly with water.
- Give the casualty 1-2 glasses of water to dilute the quantity of the substance in the stomach. (If milk is readily available, this can be given to the casualty after the water.)
- If the victim vomits of his/her own accord, bend his/her body so as to prevent vomit from entering the lungs. After vomiting, allow the victim to drink more water. Keep the victim warm and send for a doctor immediately and show SDS or label.

4.5 Likely Acute or Delayed:

• None.



Issue Date: 3 June 2013 Page 3 of 7

Version No.: 01 (Supersedes Version: 00)

Last Revision Date: 10 Nov 2010 **Product No.:** BW-64

4.6 Note to Physician:

None.

4.7 Protection of First-Aid Providers:

First-aid personnel should wear personal protection equipment when assisting the casualty.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable Fire-Extinguishing Media:

• Foam (alcohol-resistant foam), powder, and carbon dioxide are effective fire-extinguishing agents.

5.2 Unsuitable Extinguishing Media:

None under normal conditions.

5.3 Hazardous Combustion Products:

Ammonia, carbon oxides, sulfur oxides.

5.4 Special Protective Actions for Fire Fighters:

- Cool the container(s) surface that is exposed to fire by spraying the surface with water.
- When fighting the fire, wear protective equipment (i.e., respiratory masks, self contained breathing apparatus, chemical protection suit, gloves, boots, goggles, mask, etc.) as needed to avoid inhaling and/or skin contact with the chemical substance. Extinguish from the upwind direction.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment, and Emergency Measures:

- Wear protective equipment (i.e., respiratory masks, self contained breathing apparatus, chemical protection suit, gloves, boots, goggles, mask, etc.) as needed to avoid inhaling and/or skin contact with the chemical and/or vapours, if any. Work upwind, if possible.
- See Section 8 of this SDS for Personal Protective Equipment.

6.2 Environmental Precautions:

- Do not allow to enter drains, sewers or water courses.
- The chemical substance in question should not be released into the environment (water, soil).

6.3 Spill Containment and Cleaning Up:

Minor Spills

- · Avoid chemical contact by using personal protective equipment.
- Clean up spills immediately.
- Contain and absorb spill with sand, earth or other suitable absorbent material.
- Place spilled material in clean, dry, sealable, labelled container for disposal.

Major Spills

- Clear area of personnel and move upwind.
- Call SCDF or local Fire Brigade.
- Wear full body protective clothing with appropriate respiratory masks (including self contained breathing apparatus).
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or other suitable absorbent material.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise local Environmental Agency or Authority.



Issue Date: 3 June 2013 Page 4 of 7

Version No.: 01 (Supersedes Version: 00)

Last Revision Date: 10 Nov 2010 **Product No.:** BW-64

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for Safe Handling:

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

7.2 Conditions for Safe Storage:

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- · Keep out of reach of children.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters/Occupational Exposure Limits:

Ingredient	CAS No.	PEL/OEL	Source
Aluminum sulfate	10043-01-3	2 mg/m3	ACGIH TWA
Aluminum sulfate	10043-01-3	2 mg/m3	OSHA TWA
Aluminum sulfate	10043-01-3	2 mg/m3	NIOSH TWA 10 hours

8.2 Appropriate Engineering Controls:

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator.

8.3 Personal Protective Equipment:

- Use the following protective equipment as needed:
- Respiratory Protection: Self contained breathing apparatus.
- Eye Protection: Wear approved safety goggles.
- Hand Protection: Wear protective gloves. Nitrile gloves are recommended, but be aware that the liquid
 may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the
 glove supplier.
- Skin Protection: Apron and long sleeves are recommended. Wear suitable protective clothing.
- Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling
 the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective
 equipment to remove contaminants.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Appearance Physical State: Clear liquid

9.2 Colour: Colourless to slight amber

9.3 Odour: Odourless9.4 Odour Threshold: Not applicable

9.5 Property Value Notes

Melting Point 0°C Boiling Point 100°C

Flash Point Not applicable (Not flammable) Closed cup Explosive Limit Not applicable Lower limit



Issue Date: 3 June 2013 Page 5 of 7

Version No.: 01 (Supersedes Version: 00)

Last Revision Date: 10 Nov 2010 **Product No.:** BW-64

Explosive Limit Not applicable Upper limit

Vapour Pressure ~15 mmHg @ 20°C

Vapour Density Not applicable Air=1 Relative Density 1.321 25°C

Solubility in Water Completely soluble Water at 20°C

Solubility (Other) Not applicable Partition Coefficient: n-octanol/water Not applicable

Viscosity Not applicable (like water)

pH Approximately 2.00 25°C

Evaporation Rate Not applicable Butyl Acetate = 1

Flammability (Solid, Gas)

Not applicable

Auto-Ignition Temperature Not applicable (Not flammable)

Decomposition Temperature Unknown

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity/Incompatible Materials:

Strong alkali, strong oxidizing agents.

10.2 Chemical Stability:

• Stable under normal temperature and pressure.

10.3 Possibility of Hazardous Reaction:

Hazardous polymerisation will not occur.

10.4 Conditions to Avoid:

Excessive heat, contact with incompatible materials.

10.5 Hazardous Decomposition Products:

Aluminum hydroxide, sulfur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Acute Toxicity on Product Mixture:

11.2 Acute Toxicity on Ingredients:

Chemical Name	CAS No.	Acute Oral (LD50 mg/kg)	Test Animal
Aluminum sulfate	10043-01-3	1930	Rat

11.3 Skin Corrosion/Irritation:

Causes skin irritation.

11.4 Serious Eye Damage/Irritation:

Causes serious eye irritation.

11.5 Respiratory Organ or Skin Sensitisation:

None.

11.6 Germ Cell Mutagenicity:

None.

11.7 Carcinogenicity:

• None.



Issue Date: 3 June 2013 Page 6 of 7

Version No.: 01 (Supersedes Version: 00)

Last Revision Date: 10 Nov 2010 **Product No.:** BW-64

11.8 Reproductive Toxicity:

None.

11.9 Specific Target Organ Toxicity:

None.

11.10 Aspiration Hazard

Not applicable.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Ecotoxicity of Product Mixture:

No data available.

12.2 Ecotoxicity on Ingredients:

Chemical Name	CAS No.	Fish Toxicity	Marine Organism
Aluminum sulfate	10043-01-3	LC ₅₀ (24hr): 4-4.4 mg/L	Fish: Salvelinus fontinalis

12.3 Persistence and Degradability:

No data on possible environmental effects have been found.

12.4 Bioaccumulative Potential:

No data available on bioaccumulation.

12.5 Mobility

The product is water soluble and may spread in water systems.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal Method in Singapore:

• Dispose off in accordance to the Environmental Public Health (Toxic Industrial Waste) Regulations under the Environmental Protection and Management Act (EPMA).

13.2 Disposal Method Overseas:

Dispose off in accordance with all applicable local or national regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 Land (ADR):

UN Number: 3264
Class: 8, Corrosive
Subsidiary Risk: None
Packing Group: III

Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S. (contains Aluminum Sulphate

Solution)

14.2 Sea (IMDG):

UN Number: 3264
Class: 8, Corrosive
Subsidiary Risk: None
Packing Group: III

• Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S. (contains Aluminum Sulphate

Solution)

Marine Pollutant (Yes/No): No

Packing Instructions: P001, LP01

• Limited Quantity: 5L

• Further Information: Do not allow any contact with metal – danger of corrosion.



Issue Date: 3 June 2013 Page 7 of 7

Version No.: 01 (Supersedes Version: 00)

Last Revision Date: 10 Nov 2010 **Product No.:** BW-64

14.3 Sea (Annex II of MARPOL 73/78 and the IBC Code):

Pollution Category: Not applicable
 Ship Type: Not applicable
 Product Name: Not applicable

14.4 Air (IATA):

UN Number: 3264
Class: 8, Corrosive
Subsidiary Risk: None
Packing Group: III

Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S. (contains Aluminum Sulphate

Solution)

Further Information: Do not allow any contact with metal – danger of corrosion.

14.5 Special Precautions:

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1 Applicable Singapore Regulations:

- Workplace Safety and Health Act & Workplace Safety and Health (General Provisions) Regulations: This product is subject to the SDS, labelling, PEL and other requirements in the act/regulation.
- Environmental Protection and Management Act & Environmental Protection and Management (Hazardous Substances) Regulations:

This product is subject to the requirements in the act/regulation.

Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and Explosives) Regulations:
 This product is subject to the requirements in this regulation.

SECTION 16: OTHER INFORMATION

16.1 Issued By:

- FUJIFILM Asia Pacific Pte. Ltd.
- This SDS is prepared in accordance with Singapore Standard SS 586: Part 3: 2008.

16.2 Warranty

• The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions.