

# SAFETY DATA SHEET

## 1. Identification

Product identifier	Gunk Engine Protector - Shine		
Other means of identification			
SDS number	CEB1		
Part No.	CEB1		
Tariff code	3814.00.1000		
Recommended use	Protector		
<b>Recommended restrictions</b>	None known.		
Manufacturer/Importer/Supplie	r/Distributor information		
Manufacturer			
Company name Address	Blumenthal Brands Integrat 600 Radiator Road Indian Trail, NC 28079	ed, LLC	
Telephone	Customer Service/ Technical	(704) 821-7643	
Website E-mail	www.solvewithB.com sds@solvewithB.com		
Emergency phone number	INFOTRAC (Domestic) INFOTRAC (International)	(800) 535-5053 (352) 323-3500	

# 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, oral	Category 5
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Signal word Hazard statement		if swallowed. May be fatal if swallowed and enters
Hazard statement	Extremely flammable aerosol. May be harmful	if swallowed. May be fatal if swallowed and enters use drowsiness or dizziness. Toxic to aquatic life.
Hazard statement Precautionary statement	Extremely flammable aerosol. May be harmful airways. Causes serious eye irritation. May ca	use drowsiness or dizziness. Toxic to aquatic life.
Hazard statement	Extremely flammable aerosol. May be harmful airways. Causes serious eye irritation. May ca Keep away from heat/sparks/open flames/hot flame or other ignition source. Pressurized cor	use drowsiness or dizziness. Toxic to aquatic life. surfaces No smoking. Do not spray on an open ntainer: Do not pierce or burn, even after use. Avoid andling. Use only outdoors or in a well-ventilated
Hazard statement Precautionary statement	Extremely flammable aerosol. May be harmful airways. Causes serious eye irritation. May ca Keep away from heat/sparks/open flames/hot a flame or other ignition source. Pressurized cor breathing mist/vapor. Wash thoroughly after ha area. Avoid release to the environment. Wear If swallowed: Immediately call a poison center/ Remove person to fresh air and keep comforta	use drowsiness or dizziness. Toxic to aquatic life. surfaces No smoking. Do not spray on an open ntainer: Do not pierce or burn, even after use. Avoid andling. Use only outdoors or in a well-ventilated eye protection/face protection. /doctor. Do NOT induce vomiting. If inhaled: able for breathing. If in eyes: Rinse cautiously with uses, if present and easy to do. Continue rinsing.
Hazard statement Precautionary statement Prevention	Extremely flammable aerosol. May be harmful airways. Causes serious eye irritation. May ca Keep away from heat/sparks/open flames/hot s flame or other ignition source. Pressurized cor breathing mist/vapor. Wash thoroughly after ha area. Avoid release to the environment. Wear If swallowed: Immediately call a poison center/ Remove person to fresh air and keep comforta water for several minutes. Remove contact len Call a poison center/doctor if you feel unwell. I	use drowsiness or dizziness. Toxic to aquatic life. surfaces No smoking. Do not spray on an open ntainer: Do not pierce or burn, even after use. Avoid andling. Use only outdoors or in a well-ventilated eye protection/face protection. /doctor. Do NOT induce vomiting. If inhaled: able for breathing. If in eyes: Rinse cautiously with nses, if present and easy to do. Continue rinsing. f eye irritation persists: Get medical er tightly closed. Store locked up. Protect from

None known.

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

## 3. Composition/information on ingredients

ixtures			
Chemical name	Common name and synonyms	CAS number	%
Hydrotreated Light Naphthenic Distillates Petroleum		64742-53-6	20 - < 30
Soy Methyl Esters		67784-80-9	20 - < 30
Soybean Oil		8001-22-7	20 - < 30
Citrus Terpenes		94266-47-4	5 - < 10
Tripropylene Glycol Monomethyl Ether		25498-49-1	3 - < 5
Carbon Dioxide		124-38-9	1 - < 3
Poly(oxyethylene) Sorbitol Hexaoleate		57171-56-9	1 - < 3
Isopropylamine Dodecylbenzene Sulfonate		26264-05-1	< 1
Propylene Glycol		57-55-6	< 0.3
Water		7732-18-5	< 0.1

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures		
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.	
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.	
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.	
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observatio Symptoms may be delayed.	
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.	
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.	
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do no breathe fumes.	
General fire hazards	Extremely flammable aerosol.	

Material name: Gunk Engine Protector - Shine

CEB1 Version #: 07 Revision date: 03-17-2020 Issue date: 05-21-2015

#### 6. Accidental release measures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear Personal precautions, appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not protective equipment and touch damaged containers or spilled material unless wearing appropriate protective clothing. emergency procedures Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Methods and materials for Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without containment and cleaning up risk. Move the cylinder to a safe and open area if the leak is irreparable. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. **Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. 7. Handling and storage Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing Precautions for safe handling or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not taste or swallow. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Conditions for safe storage. Level 3 Aerosol. including any incompatibilities Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
Soybean Oil (CAS 8001-22-7)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	

US. ACGIH Threshold Lim Components	Туре	Value	Form
Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
Soybean Oil (CAS 8001-22-7)	TWA	5 mg/m3	Respirable mist.
8001-22-7)		10 mg/m3	Total mist
Components Propylene Glycol (CAS 57-55-6)	ntal Exposure Level (WEEL) Guides Type TWA	Value 10 mg/m3	Form Aerosol.
logical limit values	No biological exposure limits noted for	r the ingredient(s).	
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.		
ividual protection measure	s, such as personal protective equipme	ent	
Eye/face protection	Face shield is recommended. Wear safety glasses with side shields (or goggles). Applicable for industrial settings only.		
Skin protection			
Hand protection	Wear appropriate chemical resistant g	loves. Applicable for industria	l settings only.
Other	Wear appropriate chemical resistant clothing. Applicable for industrial settings only.		
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. Dust & vapor respirator. Applicable for industrial settings only.		
		vapor respirator. Applicable for	or industrial settings only.
Thermal hazards			or industrial settings only.

# 9. Physical and chemical properties

Appearance	Liquid Clear. Aerosol.			
Physical state	Liquid.			
Form	Aerosol.			
Color	Yellow-orange.			
Odor	Mild			
Odor threshold	Not available.			
рН	Not available.			
Melting point/freezing point	Not available.			

Initial boiling point and boiling range	Not available.
Flash point	172.0 °F (77.8 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.1 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.42 lbs/gal
Explosive properties	Not explosive.
Flame extension	> 30 in
Flammability (flash back)	No
Flammability class	Combustible IIIA estimated
Heat of combustion (NFPA 30B)	> 30 kJ/g
Oxidizing properties	Not oxidizing.
Refractive index	1.46
Specific gravity	0.89
VOC	7.4
40 Stability and reactivity	

# 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

## Information on likely routes of exposure


Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.

Ingestion	May be harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.		
Information on toxicological effe	ects		
Acute toxicity	May be fatal if swallowed and enters airways.		
Components	Species	Test Results	
Hydrotreated Light Naphthenic Dis	stillates Petroleum (CAS 64742-53-6)		
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg, 24 Hours	
Inhalation			
LC50	Rat	> 3.9 mg/l, 4 Hours	
<b>Oral</b> LD50	Rat	> 2000 mg/kg	
	Rai	> 2000 mg/kg	
Propylene Glycol (CAS 57-55-6) Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg, 24 Hours	
Oral			
LD50	Rat	22000 mg/kg	
Tripropylene Glycol Monomethyl E	Ether (CAS 25498-49-1)		
Acute			
Dermal			
LD50	Rabbit	15440 mg/kg, 24 Hours	
Oral		o 400 - #	
LD50	Rat	3400 mg/kg	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritati	on.	
Serious eye damage/eye irritation	Causes serious eye irritation.		
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitiza		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Not classifiable as to carcinogenicity to humans.		
	Evaluation of Carcinogenicity		
Not listed. OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1052)		
Not regulated.	ogram (NTP) Report on Carcinogens		
	thenic Distillates Petroleum Known To Be Huma	an Carcinogen.	
Reproductive toxicity	This product is not expected to cause reproductive	or developmental effects.	
Specific target organ toxicity -	May cause drowsiness and dizziness.		
single exposure Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Chronic effects	Prolonged inhalation may be harmful.		
	<b>č</b>		

12. Ecological informatio				
Ecotoxicity	Toxic to aquatic life.			
Components		Species	Test Results	
Propylene Glycol (CAS 57-55	5-6)			
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours	
Fish	LC50	Fathead minnow (Pimephales promelas)	710 mg/l, 96 hours	
Persistence and degradability	No data is av	ailable on the degradability of any ingredie	nts in the mixture.	
Bioaccumulative potential				
Partition coefficient n-octain Propylene Glycol	nol / water (log	Kow) -0.92		
Mobility in soil	No data avail	able.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
13. Disposal consideration	ons			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.			
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.			
14. Transport information	า			

\_ \_ \_

DOT		
UN number	UN1950	
UN proper shipping name	Aerosol, flammable, MARINE POLLUTANT, Limited Quantity	
Transport hazard class(es)		
Class	2.1	
Subsidiary risk	-	
Packing group	Not available.	
Environmental hazards		
Marine pollutant	Yes	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
ΙΑΤΑ		
UN number	UN1950	
UN proper shipping name	Aerosol, flammable, Limited Quantity	
Transport hazard class(es)		
Class	2.1	
Subsidiary risk	-	
Packing group	Not available.	
Environmental hazards	Yes	
ERG Code	9L	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
Other information		
Passenger and cargo	Allowed with restrictions.	
aircraft		
Cargo aircraft only	Allowed with restrictions.	
IMDG		
UN number	UN1950	
Material name: Gunk Engine Protector - Shine		



Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

### SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

#### **US state regulations**

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Hydrotreated Light Naphthenic Distillates Petroleum (CAS 64742-53-6)

#### International Inventories

Country(s) or region	Inventory name On in	ventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates that all compo	nents of this product comply with the inventory requirements administered by the governing c	ountry(s)

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	05-21-2015
Revision date	03-17-2020
Version #	07
HMIS® ratings	Health: 3 Flammability: 4 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 4 Instability: 0
NFPA ratings	2 0

	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Physical & Chemical Properties: Multiple Properties