ACTI-KLEAN (revised September 2010)

Material Safety Data Sheet

		SECTION I - (COMPANY IDENTIFIC	ATION			
PRODUCT: ACTI-KLEAN				CAT. NO.: AK-1, AK-5, AK-55			
MANUFACTURED BY: Sporlan Division- Parker Hannifin Corporation 206 Lange Drive Washington, MO 63090				TELEPHONE NUMBERS: Office: 1-(636)-239-1111 Emergency Only: 1-(800) 424-9300			
SECTION II - HAZARDOUS INGREDIENTS							
OSHA Hazardous Components (29 CFR 1910.1200)				EXPOSURE LIMITS: 8 HR. TWA OSHA PEL ACGIH TLV			
Ethylene gylcol monobutyl ether (CAS# 111-76-2) Dodecylbenzene sulfonic acid (CAS# 27176-87-0)				25 ppm (skin) NE	25 ppm NE	(skin)	
		SECTION III - I	HAZARDS IDENTIFIC	ATIONS			
EMERGENCY OVERVIEW: WARNING! Eye and skin irritant. Harmful if swallowed or inhaled. POTENTIAL HEALTH EFFECTS: Inhalation of vapors in high concentration may cause headache, nausea, vomiting. INHALATION: Inhalation of vapors in high concentration may cause headache, nausea, vomiting. EYE CONTACT: Irritation develops immediately on contact. SKIN CONTACT: Irritation develops on contact. INGESTION: Harmful if swallowed. May cause headache, nausea, vomiting. CHRONIC Effects: Not established. NOTE: Intervention							
	DGENICITY: LISTED	D IN NTP? No	IARC? N	lo	OSHA R	egulated? No	
SECTION IV - FIRST AID MEASURES							
NHALATION: Remove victim to fresh air and, if needed, immediately begin artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. Contact a physician immediately. EYE CONTACT: Flush eyes with water for 15 minutes. Get medical attention if symptoms develop and persist. SKIN CONTACT: Flush with water or soap and water for 15 minutes or until all traces have been removed. Seek medical attention if symptoms develop and persist. NGESTION: Do not induce vomiting. Rinse mouth out with water. Get immediate medical attention.							
		SECTION V -	FIRE FIGHTING MEA	SURES			
FLASHPOINT (TEST METHOD): Not flammable - aqueous solution. FLAMMABLE LIMITS: NA LOWER: NA AUTOIGNITION TEMPERATURE: NE GENERAL HAZARD: FIRE FIGHTING INSTRUCTIONS:			ide. Avoid breathing sr	UPPER: NA smoke, fumes, mist, or vapors on the downwind side. Firefighters			
EXTINGUISHING MEDIA: Dry powder, carbon dioxide (CO ₂), water fog or spray. HAZARDOUS COMBUSTION PRODUCTS: Acrid smoke, irritating and toxic fumes of SO _x , H ₂ S, PO _x .							
SECTION VI - ACCIDENTAL RELEASE MEASURES							
LAND SPILL: WATER SPILL:	LARGE SPILLS: Pick up with absorbent media, place in non-leaking containers for proper disposal or reuse.						
SECTION VII - HANDLING AND STORAGE							
HANDLING: STORAGE:	Avoid contact with skin, eyes, and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown in section IV. Launder contaminated clothing before reuse. Store away from food stuffs.						
SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION							
ENGINEERING CONTROLS: Local exhaust ventilation. PERSONAL PROTECTION: Respiratory protection not normally needed under normal conditions of use. Use rubber or latex gloves, chemical goggles or full face shields. Use boots, aprons, drench showers, eye wash as needed for protection against spills and/or splashes.							
SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES							

VAPOR PRESSURE: ND SPECIFIC GRAVITY (H₂O=1): 1.02 SOLUBILITY IN WATER: Complete VAPOR DENSITY (Air=1): ND EVAPORATION RATE (BuAc=1): <1 VOC (G/L):

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable. High temperatures. CONDITIONS TO AVOID: MATERIALS TO AVOID: Oxidizers. HAZARDOUS DECOMPOSITION PRODUCTS: SO_x , H_2S , PO_x and from combustion - smoke and toxic fumes. HAZARDOUS POLYMERIZATION: Will not occur.

	SECTION XI - TOXICOLOGICAL INFORMATION					
Ethylene Glycolmonobutylether Dodecyl benzene sulfonic acid	TDLo: 600 mg/kg (oral - wmn) TCLo: 195 ppm/8hr (inh - human) GIT TCLo: 100 ppm (inh - human) NOSE, E' LD50: 470 mg/kg (oral - rat) LC50: 2900 mg/m ³ (inh - rat) LD50: 50-500 mg/kg (oral - mouse)	YE, CNS				
	SECTION XII - ECOLOGICAL INFORMATION					
Harmful to aquatic life in very low concentrations.		1000 ppm / 24 hr / brine shrimp / TLm 5 - 15 ppm / guppy / lethal conc.				
	SECTION XIII - DISPOSAL CONSIDERATIONS					
Dispose as hazardous waste. Classification and c	ocumentation is required before disposal. Follow all local, state and fe	deral regulations.				
SECTION XIV - TRANSPORTATION INFORMATION						
PROPER SHIPPING NAME: Non-regulated mathematical strength strengt						
	SECTION XV - REGULATORY INFORMATION					
CERCLA (Comprehensive Environmental Res	I benzene sulfonic acid). Contact local authorities for other reporting r Reauthorization Act): Not listed.	equirements.				
SECTION XVI - OTHER INFORMATION						
State Right-to-Know Programs: MA, NJ, PA NFPA Ratings Health: 1 Flammability: 0 Reactivity: 0						

HMIS Protective Equipment: X See your supervisor

Prepared by: Sporlan Division- Parker Hannifin Corporation

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Parker Hannifin Corporation. The data on this sheet related only to specific material designated herein. Parker Hannifin assumes no legal responsibility for use or reliance upon these data.