

SAFETY DATA SHEET Sta Put Aerosol

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name Sta Put Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Spray Adhesive

1.3. Details of the supplier of the safety data sheet

Supplier Sanglier Limited
Shelley Close
Lowmoor Business Park
Kirkby In Ashfield
NG17 7JZ
Tel: 01623 722661 (Mon-Fri 09:00 -17:00)
Fax: 01623 885971
E-mail:- Technical@sanglier.org.uk

1.4. Emergency telephone number

National Emergency Telephone Number
UK +44 (0)1623 722 661 (Monday - Friday 09:00 - 17:00)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Aerosol 1 - H222
Human health	Carc. 2 - H351
Environment	Aquatic Chronic 3 - H412

Classification (1999/45/EEC) Carc. Cat. 3;R40. F+;R12. R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

Limited evidence of a carcinogenic effect.

Environment

Not regarded as a environmental hazard under current legislation.

Physical and Chemical Hazards

Pressurised container: Must not be exposed to temperatures above 50C.

2.2. Label elements

Contains DICHLOROMETHANE

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements

H222	Extremely flammable aerosol.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P273	Avoid release to the environment.
P281	Use personal protective equipment as required.

Sta Put Aerosol

P410+412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P501	Dispose of contents/container in accordance with national regulations.
Supplementary Precautionary Statements	
P251	Pressurized container: Do not pierce or burn, even after use.
P308+313	IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

DICHLOROMETHANE	30-60%
CAS-No.: 75-09-2	EC No.: 200-838-9
Classification (EC 1272/2008) Carc. 2 - H351	Classification (67/548/EEC) Carc. Cat. 3;R40
PROPANE	10-30%
CAS-No.: 74-98-6	EC No.: 200-827-9
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
BUTANE/ISOBUTANE	10-30%
CAS-No.: 106-97-8	EC No.:
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) F+;R12.
HEXANE MIXTURE OF ISOMERS (MAX 5% n-HEXANE (203-777-6))	1-5%
CAS-No.: -	EC No.: -
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) F;R11 Xn;R65 Xi;R38 R67 N;R51/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once.

Inhalation

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention. Get medical attention.

Ingestion

Rinse mouth thoroughly. DO NOT induce vomiting. Get medical attention immediately.

Sta Put Aerosol

Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Known or suspected carcinogen for humans.

Inhalation.

Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation.

Skin contact

Acts as a defatting agent on skin. Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Water spray, fog or mist. Carbon dioxide or dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

Forms explosive mixtures with air. Extremely flammable. May explode in a fire. May travel considerable distance to source of ignition and flash back.

Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Use water spray to reduce vapours. Use water to keep fire exposed containers cool and disperse vapours. Containers close to fire should be removed immediately or cooled with water.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Collect and dispose of spillage as indicated in section 13.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth and place into containers. Use sealed containers for reclamation or dispose of at a licenced hazardous waste collection point. Avoid contact with water.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Store at moderate temperatures in dry, well ventilated area.

Sta Put Aerosol

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE/ISOBUTANE	OES	600 ppm		750 ppm		
DICHLOROMETHANE	WEL	100 ppm(Sk)	350 mg/m3(Sk)	300 ppm(Sk)	1060 mg/m3(Sk)	
PROPANE		Asphyxiating		Asphyxiating		

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Process conditions

Ensure suitable ventilation of area. Use engineering controls to reduce air contamination to permissible exposure level.

Engineering measures

Provide adequate ventilation.

Respiratory equipment

Respiration equipment only required if ventilation is inadequate

Hand protection

Protective gloves should be used if there is a risk of direct contact or splash. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protection

Provide eyewash station.

Hygiene measures

Eating, smoking and water fountains prohibited in immediate work area. Wash promptly if skin becomes contaminated.

Personal protection

Wear protective work clothing.

Skin protection

Wear suitable gloves if prolonged or repeated skin contact is likely

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Aerosol container containing a mixture of active ingredients, solvents and propellants
Colour	Light (or pale). Amber.
Odour	Characteristic. of solvents
Solubility	Insoluble in water
Comments	A flash point method is not available for aerosols but the major hazardous component, the Propellant has a flash point of <-40 C with flammability limits of 9.5% vol. upper and 1.8% vol. lower. Auto ignition temperature is 410/580 C.

9.2. Other information

Not available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product. Stable under recommended transport or storage conditions.

Sta Put Aerosol

10.2. Chemical stability

Highly volatile

10.3. Possibility of hazardous reactions

No known hazardous reactions if stored under normal conditions.

Hazardous Polymerisation

Will not polymerise.

10.4. Conditions to avoid

Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials To Avoid

Aluminium Caution can dissolve plastic and rubber materials

10.6. Hazardous decomposition products

In combustion emits toxic fumes

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

General information

Known or suspected carcinogen for humans. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation.

Ingestion

Ingestion may cause similar symptoms to that of inhalation.

Skin contact

Contains components which may penetrate the skin. Harmful: danger of serious damage to health by prolonged exposure in contact with skin.

Eye contact

Extreme irritation of eyes and mucous membranes, including burning and tearing.

Health Warnings

Prolonged inhalation of high concentrations may damage respiratory system. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Route of entry

Inhalation. Skin absorption.

Target Organs

Blood Central nervous system Respiratory system, lungs Liver

Medical Symptoms

Narcotic effect. Drowsiness. Dizziness.

Specific effects

Contains a substance/a group of substances which may cause cancer by inhalation.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product is not expected to be hazardous to the environment.

12.1. Toxicity

Not regarded as dangerous for the environment

Sta Put Aerosol

12.2. Persistence and degradability

Degradability

The degradability of the product has not been stated.

12.3. Bioaccumulative potential

Bioaccumulative potential

Dichloromethane has low bioaccumulative potential

12.4. Mobility in soil

Mobility:

The product is volatile, insoluble with water and is heavier than water.

12.5. Results of PBT and vPvB assessment

Not determined

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not puncture or incinerate even when empty. Ensure containers are empty before discarding (explosion risk). Dispose of waste and residues in accordance with local authority requirements.

13.1. Waste treatment methods

Ensure container is empty and dispose of in accordance with Local Authority regulations. Do not pierce or incinerate even when container is empty.

Waste Class

Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues). Empty Aerosol: 15 01 04 (No hazardous residues).

SECTION 14: TRANSPORT INFORMATION

General

This product is packed in accordance with the Limited quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow the transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing they are labelled in accordance with the requirements of those regulations to show that they are transported as Limited Quantities. Aerosols not so packed must show the following.

14.1. UN number

UN No. (ADR/RID/ADN) 1950

14.2. UN proper shipping name

Proper Shipping Name AEROSOLS

14.3. Transport hazard class(es)

ADR/RID/ADN Class 2, 5F
ADR/RID/ADN Class Class 2.1: Flammable gases.
ADR Label No. 2.1
IMDG Class 2.1
ICAO Class/Division 2.1
Transport Labels



14.4. Packing group

Sta Put Aerosol

ADR/RID/ADN Packing group #
IMDG Packing group #
ICAO Packing group #

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS F-D, S-U
Tunnel Restriction Code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Uk Regulatory References

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Health and Safety at Work Act 1974.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. EU Legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). The Aerosol Dispensers Regulations 2009 (SI 2824) Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007). Control of Substances Hazardous to Health Regulations 2002 (as amended) The Aerosol Dispensers (EEC Requirements)(Amendment) Regulations 1996 (S.I 1996 No. 2421). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Issued By Technical Service Manager
Revision Date 10-12- 2012
Revision 3
Supersedes date 28-09- 2012
SDS No. 11265
Date 10-12- 2012

Sta Put Aerosol

Risk Phrases In Full

R12	Extremely flammable.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

H315	Causes skin irritation.
H222	Extremely flammable aerosol.
H220	Extremely flammable gas.
H412	Harmful to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.